

THETFORD 12V Compressor refrigerators

	T2090	T2138	T2152	T2160	T2175
					
Main dimensions (HxWxD)*	975 x 418 x 486 mm	1598 x 418 x 503mm	1500 x 418 x 569 mm	1245 x 525 x 563 mm	1245 x 525 x 613 mm
Recommended built-in depth	506 mm	506 mm	570 mm	563 mm	613 mm
Total volume	84 L	138 L	150 L	158 L	174 L
Volume frozen food compartment	6,1 L	11,6 L	17 L	30,5 L	33,5 L
Location frozen food compartment	Internal	Internal	Internal	External drawer	External drawer
Energy consumption**	0,35 kW/24h	0,50 kWh/24h	0,46 kWh/24h	0,56 kWh/24h	0,56 kWh/24h
Average ampere usage	26,6 Ah/24h	42,0 Ah/24h	39,1 Ah/24h	45,8 Ah/24h	46,5 Ah/24h
Climate class Day Mode	N (16 °C - 32 °C)	SN- T (10°C - 43°C)	SN- T (10°C - 43°C)	SN- T (10°C - 43°C)	SN- T (10°C - 43°C)
Climate class Night mode	N (16 °C - 32°C)	SN (10 °C - 32°C)	SN (10 °C - 32°C)	SN (10 °C - 32°C)	SN (10 °C - 32°C)
Noise levelb - Day Mode	34.9 dB (A)	34.2 dB (A)	35.6 dB (A)	35.6 dB (A)	33.6 dB (A)
Noise levelb - Night mode	33.1 dB (A)	31.5 dB (A)	32.3 dB (A)	32.3 dB (A)	32.3 dB (A)
Net weight	21,1 kg	34,2 kg	35,0 kg	37,4 kg	38,4 kg
Door type hinging	Right hinge	Right hinge	Right hinge	Right hinge	Right hinge
Door	Flat Framed	Flat Framed	Flat Framed	Flat Framed	Flat Framed
Door panel	Matte Black	Matte Black	Matte Black	Matte Black	Matte Black
Amount of shelves	3	3	3	3	3
Slide-out box	No	Yes	Yes	Yes	Yes
Display	Capacitive touch	Capacitive touch	Capacitive touch	Capacitive touch	Capacitive touch
Part number	692932SP	692935SP	692937SP	692943SP	692946SP

* Including protruding door handle of 11 mm.

** According IEC62552-2020 part 3.